
BOOT ROM
44
SCREEN
46
48
DSP
50
DMA
52
ARBITER /DECODER
54
EXTERNAL MEMORY
56
PAGE TABLE(S)
58
I/O INT
60
62
KEY STORAGE
64
66
EXTERNAL BUS
70
EBI
42
DMA
32
ETM
26
22
VIC
21
INV
INT
JTAG CTRL
18
ICE
24
20
ALU
16
14
12
CORE
10
MEMORY MGMT
30
CACHE
38
TCM
36
CPIS
34
40
SYSTEM BUS

FIG. 1


Non-Secure
Secure
Monitor
72
NS OS
74
Secure Kernal
80
NS Ap1
NS Ap2
S Ap1
S Ap2
76
78
82
84

Fig. 2


Domain
Non-secure
Secure
Monitor
Mode
1
NSMode1
SMode1
2
NsMode2
SMode2

Fig. 3



Fig. 4



Fig. 5



// = private to mode

Fig. 6



Fig. 7



Fig. 8


Non secure
Secure
thread 1
IRQ handler / scheduler
Events
secure world entry/exit
secure thread 1
return function
user mode
IRQ mode
monitor mode
user mode
monitor mode
1
2
SMI
3
start appli
4
SMI
5
SUBS
6
End of thread

Fig. 9


monitor
SIRQ
IRQ
svc
system
abort
undef
irq
fiq
user
svc
system
abort
undef
irq
fiq
user
IRQ
SIRQ

Fig. 10


Secure
Events
Non secure
Secure IRQ handler
IRQ mode
secure thread 1
user mode
secure world entry / exit
monitor mode
IRQ handler
IRQ mode
thread 1
user mode
start appli
IRQ / FIQ
SUBS
SMI
SMI
SMI
SUBS
End of thread
1
2
3
4
5
6
7
8
9
10
11

Fig 11A


Secure
Non secure
Events
IRQ handler
thread 1
IRQ mode
user mode
secure world entry / exit
monitor mode
secure thread 1
user mode
Secure IRQ handler
IRQ mode
SIRQ
SMI
SUBS
End of thread
1
2
3
4
5
6

Fig. 11B


Non secure
Events
Secure
thread 1
user mode
IRQ handler
IRQ mode
secure world entry / exit
monitor mode
secure thread 1
user mode
Secure IRQ handler
IRQ mode
1
2
SMI
3
start appli
4
IRQ / FIQ
5
SMI
6
7
SUBS
8
SMI
9
10
SMI
11
SUBS
12
End of thread

Fig. 13A



Fig. 12



Fig. 13B

Exception	Vector offset	Corresponding mode
Reset	0x00	Supervisor mode
Undef	0x04	Monitor mode / Undef mode
SWI	0x08	Supervisor mode / Monitor mode
Prefetch abort	0x0C	Abort mode / Monitor mode
Data abort	0x10	Abort mode / Monitor mode
IRQ / SIRQ	0x18	IRQ mode / Monitor mode
FIQ	0x1C	FIQ mode / Monitor mode
SMI	0x20	Undef mode / Monitor mode

Fig. 14

Monitor

Reset	VM0
Undef	VM1
SWI	VM2
Prefetch abort	VM3
Data abort	VM4
IRQ/SIRQ	VM5
FIQ	VM6
SMI	VM7

Secure

Reset	VS0
Undef	VS1
SWI	VS2
Prefetch abort	VS3
Data abort	VS4
IRQ/SIRQ	VS5
FIQ	VS6
SMI	VS7

Non-Secure

Reset	VNS0
Undef	VNS1
SWI	VNS2
Prefetch abort	VNS3
Data abort	VNS4
IRQ/SIRQ	VNS5
FIQ	VNS6
SMI	VNS7

Fig. 15

CP15 Monitor Trap Mask Register

only NS world exceptions illustrated



OR via hardware/external pin

1 = Mon(S)

0 = NS

Fig. 16


Start
Instruction attempting CPSR → Monitor?
98
N
Y
Generate CPSR violation exception
100
Run monitor program in monitor mode starting at CPSR violation entry point
102
Stop

Fig. 17


non-secure mode
monitor mode (interrupts disabled)
secure mode
task A
SMI
start of code C
enable interrupts
IRQ task B
task B
finished
SMI
start of code C
enable interrupts
interrupts disabled
interrupts enabled

Fig. 18


Non-secure mode
monitor mode (interrupts disabled)
secure mode
task A
SMI
start of code C
enable interrupts
IRQ task B
task B
finished
fix-up routine
SMI
start of code C

Fig. 19


non-secure mode
monitor mode
(interrupts enabled)
secure mode
task A
SMI
disable interrupts

Fig. 20


Monitor
Monitor mode
Supervisor
FIQ
IRQ
Undef
Abort
System
Privileged modes
User
Non-privileged mode
Supervisor
FIQ
IRQ
Undef
Abort
System
Privileged modes
User
Non-privileged mode

FIGURE 21

User	System	Supervisor	Abort	Undefined	Interrupt	Fast Interrupt
R0	R0	R0	R0	R0	R0	R0
R1	R1	R1	R1	R1	R1	R1
R2	R2	R2	R2	R2	R2	R2
R3	R3	R3	R3	R3	R3	R3
R4	R4	R4	R4	R4	R4	R4
R5	R5	R5	R5	R5	R5	R5
R6	R6	R6	R6	R6	R6	R6
R7	R7	R7	R7	R7	R7	R7
R8	R8	R8	R8	R8	R8	R8_fiq
R9	R9	R9	R9	R9	R9	R9_fiq
R10	R10	R10	R10	R10	R10	R10_fiq
R11	R11	R11	R11	R11	R11	R11_fiq
R12	R12	R12	R12	R12	R12	R12_fiq
R13	R13	~~R13_svc~~	~~R13_abt~~	R13_und	R13_irq	R13_fiq
R14	R14	~~R14_svc~~	~~R14_sbt~~	R14_und	R14_irq	R14_fiq
PC	PC	PC	PC	PC	PC	PC

CPSR	CPSR	CPSR	CPSR	CPSR	CPSR	CPSR
		SPSR_svc	SPSR_abt	SPSR_und	SPSR_irq	SPSR_fiq

Monitor
R0
R1
R2
R3
R4
R5
R6
R7
R8
R9
R10
R11
R12
R13_mon
R14_mon
PC

CPSR
SPSR_mon

FIGURE 22



FIGURE 23





S = 1

Fig. 24


monitor
S = 1
reset
non-secure os
non-secure tasks
secure os
secure tasks
S = 0

Fig. 25


Non-Secure
Monitor
Secure
1
NSA
2
3
4
5
SA
irq
6
7
8
9
irq handler
10
timer interrupt
NSA
thread switch
NSE
11
12
13
14
software faked interrupt
(return, threadID, parameter1, parameter2)
15
return interrupt handler
16
thread switch
17
SB

Fig. 26


Non-Secure
Monitor
Secure
1
NSA
2
3
4
5
SA
irq
6
7
8
9
irq handler
10
NSA
11
12
13
software faked interrupt
14
return interrupt handler
15
SA

Fig. 27


Start
Commence return interrupt handler
4002
Is return thread from software faked interrupt equal to currently executing secure thread?
4004
N
Y
Save context of old secure thread
4008
Resume secure thread
4006
Switch to new secure thread
4010
End

Fig. 28


Non-Secure
Monitor
Secure
NSA
SMI call
1
2
SMI call
3
4
SA
NS Thread ID
S Thread ID
parameter 1
parameter 2
Call
5
6
7
8
NSA
SMI call
9
10
SMI call
11
12
SA

Fig. 29


Non-Secure
Monitor
Secure
NSA
SMI call
1
2
SMI call
3
4
SA
5
6
7
8
NS Thread ID
S Thread ID
parameter 1
parameter 2
Call
NSA
9
task switch
10
NSB
SMI call
11
12
SMI call
13
14
task switch
15
SB

Fig. 30


Start
Call received
4012
Is call to currently active secure thread?
4014
N
Y
Is new thread available?
4018
N
Y
Save context of old secure thread
4022
Switch to new secure thread
4024
Reject call
4020
Resume currently active secure thread
4016
End

Fig. 31


Non-Secure
Monitor
Secure
SA
Int 1
Int 1 handler
Int 2
Int 2 handler
task switch
NSB

Fig. 32


Non-secure
Monitor
Secure
SA
Int 1
Stub Int 1 handler
Int 1 handler
Int 2
Int 2 handler
Resume Stub Int1 handler
Int 1 handler
Close Stub Int1 handler
Resume SA

Fig 33

Interrupt Type / Priority	How Handled
1	S
2	S
3	NS
4	NS/S
5	NS
6	NS/S
7	NS
⋮	⋮

no S only handlers lower than highest NS handler

Fig. 34


To System (Fig 1)
2010
2015
0
1
Mode = Monitor
PROCESSOR CONFIGURATION DATA
CPIS REGISTERS
34
MONITOR MODE SPECIFIC PROCESSOR CONFIGURATION DATA
2000

FIG. 35


SMI INSTN ISSUED ?
2020
ENTER MONITOR PROGRAM IN MONITOR MODE (MONITOR MODE SPECIFIC PROCESSOR CONFIGURATION DATA USED)
2030
SAVE STATE FROM DOMAIN ISSUING SMI INSTRUCTION
2040
SWITCH STATE POINTER TO POINT TO MEMORY CONTAINING STATE FOR DESTINATION DOMAIN
2050
LOAD STATE FOR DESTINATION DOMAIN
2060
EXIT MONITOR PROGRAM, EXIT MONITOR MODE AND SWITCH TO MODE IN DESTINATION DOMAIN
2070

FIG. 36


230
abort
cachable, bufferable
232
200
202
204
access permission
region attribute
208
210
virtual address
μTLB
242
main TLB
descriptors
translation table walk
CORE
234
206
246
248
244
MMU
10
physical address
238
222
non-secure
partition checker
220
236
access permission
224
240
secure
region attribute
226
MPU
cachable, bufferable

FIG. 37


cachable,
bufferable
232
230
abort
200
202
204
access
permission
region attribute
208
210
246
248
CORE
μTLB
242
main
TLB
descriptors
translation
table walk
206
234
244
partition
checker
222
MMU
10
238

FIG. 38


program generates virtual address (VA)
300
secure
non-secure
secure descriptor µTLB lookup
302
miss
secure descriptor main TLB lookup
304
miss
page table walk
306
main TLB contains the valid tagged secure descriptor
308
hit
hit
load µTLB with sub-section that contains PA
310
access permission checked (priv/user...)
312
violation ?
314
Yes
No
non-secure descriptor µTLB lookup
320
miss
non-secure descriptor main TLB lookup
322
miss
page table walk
324
main TLB contains the valid tagged non-secure descriptor
326
hit
hit
Partition checker checks if non-secure PA is non Secure
328
yes
violation ?
330
Secure/Non-secure fault ABORT
332
no
load µTLB with sub-section that contains PA
334
access permission checked (priv/user...)
336
violation ?
338
Yes
No
access permission fault ABORT
316
memory access
318

FIG. 39


core generates physical address
350
MPU checks permissions and if non-secure physical address is in non-secure memory
352
354
violation ?
Yes
356
access permission fault ABORT
No
memory access in secure or non-secure memory
358

FIG. 40


NS
370
376
PA
VA
NS
372
378
S
374
NS
VA
PA
380
S
the descriptor describes a section that overlaps Secure regions
If VA corresponds to PA in secure memory
=> partition checker generates an ABORT
If VA corresponds to PA in non-secure memory
=> this region is loaded in uTLB
Secure memory
Non-secure memory

FIG. 41


non-secure memory
395
non-secure pages table
descriptor
descriptor
descriptor
descriptor
descriptor
397
non-secure translation table base address
390
secure memory
400
405
secure pages table
descriptor
descriptor
descriptor
descriptor
407
secure translation table base address
non-secure memory
non-secure page
non-secure page
390
shared memory
410
secure memory
400
secure page
secure page

FIG. 42


TLB
Descriptor
ASID
Domain
P1 NS
P2 S
P1 S
P3 NS
P2 S
P1 S
P1 NS
P1 NS
P3 NS
P1 NS
435
430
425
Descriptors currently in the TLB
208
check domain
1/ As the core is running in secure domain, only the descriptors belonging to the secure kernel are selected
440
445
448
Descriptors belonging to current running world
check ASID
2/ Only the descriptors associated with the current ASID are selected
450
HIT or MISS
Descriptors belonging to current running process (ASID)

FIG. 43


Free memory for OS
Non-secure Privileged only (region 0)
460
Free memory for secure kernel
Secure Privileged only (region 1)
462
Secure allocated memory for secure application
Secure User and Privileged (region 2)
464

FIG. 44


No access
Non-secure page
Non-secure page
non-secure MMU
memory mapping
460
Non-secure page
Non-secure page
Non-secure page
Non-secure page
Secure
Privileged only
(region 1)
462
Secure
User and Privileged
(region 2)
464

FIG. 45


No access
Shared memory
Secure User and Privileged (region 3)
466
Non-secure page
460
Non-secure page
Non-secure page
Non-secure page
Non-secure page
Secure Privileged only (region 1)
462
Secure User and Privileged (region 2)
464

FIG. 4b


470
DEVICE 1
(SECURE/NON-SECURE)
5 BIT
476
ARBITER
472
DEVICE 2
(NON-SECURE)
478
DECODER
492
PARTITION
CHECKER
474
MEMORY
480
SCREEN
482
484
I/O
INTERFACE
486
490
488
DEVICE BUS

FIG. 47


470
DEVICE 1
(SECURE/NON-SECURE)
5 BIT
476
ARBITER
472
DEVICE 2
(NON-SECURE)
478
DECODER
474
MEMORY
480
SCREEN
482
484
I/O
INTERFACE
486
490
488
DEVICE BUS

Fig. 48



Figure 59



FIG. 49


10
CORE
VA
2153
DATA
2190
2150
MMU 1
2157
μTLB
2155
MAIN TLB
2160
TRANSLATION TABLE WALK
2165
IA
2167
PAGE TABLE DATA
2170
MMU 2
μTLB
2175
MAIN TLB
2180
TRANSLATION TABLE WALK
2185
PA
2192
PA
2194

FIG 50A


10
CORE
VA
2153
DATA
2190
μTLB
2155
MAIN TLB
2160
TRANSLATION TABLE WALK
2165
MMU 1
2150
PAGE TABLE DATA
IA
2167
μTLB
2175
MAIN TLB
2180
TRANSLATION TABLE WALK
2185
MMU 2
2170
PAGE TABLE DATA
PA
2194
PA
2192

FIG 50B


2200
2270
NON-SECURE DOMAIN
2275
0
INTERMEDIATE ADDRESS SPACE
NS
2250
PAGE TABLES FOR MMU 2
2230
2220
2210
NS
S
NS
S
PHYSICAL ADDRESS SPACE
2240
2260
SECURE DOMAIN
S
INTERMEDIATE ADDRESS SPACE
0
2265

FIG 51


2200
2250
2230
2220
2300
2210
2240
PAGE TABLES FOR MMU 2
NS
S
NS
S
NS
S
NS
2310
PHYSICAL ADDRESS SPACE
2270
2275
2315
0
NON-SECURE DOMAIN
NS
INTERMEDIATE ADDRESS SPACE
2260
2265
2305
0
SECURE DOMAIN
S
INTERMEDIATE ADDRESS SPACE

FIG 52


PA
2400
2440
2422
2420
MAIN TLB
μTLB
MMU
2410
2436
VA
EXCEPTION
2450
10
CORE

FIG 53


2500
TLB MISS EXCEPTION DETECTED ?
N
Y
ENTER MONITOR MODE AT PREDETERMINED VECTOR FOR THE EXCEPTION
2510
RETRIEVE FAULTING VA THAT CAUSED EXCEPTION
2520
DETERMINE IA FOR RELEVANT FIRST DESCRIPTOR IN FIRST TABLE
2530
REFERENCE SECOND TABLE TO OBTAIN PA FOR FIRST DESCRIPTOR
2540
FETCH FIRST DESCRIPTOR TO OBTAIN IA FOR FAULTING VA
2550
REFERENCE SECOND TABLE TO FIND SECOND DESCRIPTOR GIVING PA FOR IA OF FAULTING VA
2560
FETCH SECOND DESCRIPTOR TO OBTAIN PA FOR FAULTING VA
2570
MERGE FIRST AND SECOND DESCRIPTORS TO GENERATE NEW DESCRIPTOR GIVING VA TO PA TRANSLATION
2580
2590
STORE NEW DESCRIPTOR IN TLB
RETURN FROM EXCEPTION
2595

FIG 54


70
Address
Control
Data
2660
Data
abort
2670
38
External memory
56
Secure peripheral
470
Non-Secure peripheral
472
Core
Address
Core domain state
Descriptor 1
Descriptor 2
Descriptor (n-1)
Descriptor n
S
NS
MMU
435
425
200
10
40
Line 1
Line 2
Line (n-1)
Line n
2600
Cache
2602
2680
Data
S TAG
EBI
2632
HPROT
S TAG
Abort
2636
2634
2650
Arbiter
2652
Decoder
2654
Partition checker
2656
HPROT
S TAG
Abort
2610
TCM
2612
36
42
2620
2630
2640

FIG 55


230
abort
cachable,
bufferable
232
202
204
200
access
permission
region attribute
208
210
248
CORE
virtual
address
µTLB
main
TLB
descriptors
translation
table walk
234
206
242
246
MMU
10
238
236
physical
address

FIG 5G


2700
Non-secure program generates virtual address (VA)
2705
UTLB lookup
hit
miss
2710
NS descriptor main TLB lookup
hit
miss
2715
page table walk
2720
main TLB contains a valid tagged NS descriptor
2725
load UTLB with section that contains PA
2730
UTLB checks access permission (priv/user)
2735
violation ??
Yes
2740
access permission fault ABORT
No
2745
cacheable
No
Yes
2750
cache lookup
miss
hit
2755
secure line tag violation
Yes
2760
secure violation fault ABORT
No
2765
Cache linefill external access
2770
secure partition violation
Yes
2775
secure violation fault external ABORT
No
2780
Cache linefill
2785
data access
2790
external access
Yes
2795
secure partition violation
No
Done in MMU
Done by partition checker
Done by cache

FIG 57


2800
secure program generates virtual address (VA)
2805
uTLB lookup
hit
miss
2810
secure descriptor main TLB lookup
hit
miss
2815
page table walk
2820
main TLB contains the valid tagged secure descriptor
load uTLB with section that contains PA
2825
uTLB checks access permission (priv/user...)
2830
2835
violation
Yes
2840
access permission fault ABORT
No
2845
cacheable
No
Yes
2850
cache lookup
miss
hit
2865
Cache linefill external access
external access
2890
2880
Cache linefill
2885
data access
Done in MMU
Done by cache

FIG 58

Method of entry	How to program?	How to enter?	Entry mode
Breakpoint hits	Debug TAP or software (CP14)	Program breakpoint register and/or context-ID register and comparisons succeed with Instruction Address and/or CP15 Context ID ([2]).	Halt/monitor ([1])
Software breakpoint instruction	Put a BKPT instruction into scan chain 4 (Instruction Transfer Register) through Debug TAP or Use BKPT instruction directly in the code.	BKPT instruction must reach execution stage.	Halt/monitor
Vector trap breakpoint	Debug TAP	Program vector trap register and address matches.	Halt/monitor
Watchpoint hits	Debug TAP or software (CP14)	Program watchpoint register and/or context-ID register and comparisons succeed with Instruction Address and/or CP15 Context ID ([2]).	Halt/monitor ([1])
Internal debug request	Debug TAP	Halt instruction has been scanned in.	Halt
External debug request	Not applicable	EDBGRQ input pin is asserted.	Halt

([1]): In monitor mode, breakpoints and watchpoints cannot be data-dependent.

([2]): The cores have support for thread-aware breakpoints and watchpoints in order to enable secur debug on some particular threads.

Figure 60

Name	Meaning	Reset value	Access	Inserted in scan chain for test
Monitor mode enable bit	0: halt mode 1: monitor mode	1	R/W by programming the ICE by the JTAG (scan1) ▪ R/W by using MRC/MCR instruction (CP14)	yes
Secure debug enable bit	0: debug in non-secure world only. 1: debug in secure world and non-secure world	0	In functional mode or debug monitor mode: R/W by using MRC/MCR instruction (CP14) (only in secure supervisor mode) In Debug halt mode: No access – MCR/MRC instructions have any effect. (R/W by programming the ICE by the JTAG (scan1) if JSDAEN=1	no
Secure trace enable bit	0: ETM is enabled in non-secure world only. 1: ETM is enabled in secure world and non-secure world	0	In functional mode or debug monitor mode: R/W by using MRC/MCR instruction (CP14) (only in secure supervisor mode) In Debug halt mode: No access – MCR/MRC instructions have any effect. (R/W by programming the ICE by the JTAG (scan1) if JSDAEN=1	no
Secure user-mode enable bit	0: debug is not possible in secure user mode 1: debug is possible in secure user mode	1	In functional mode or debug monitor mode: R/W by using MRC/MCR instruction (CP14) (only in secure supervisor mode) In Debug halt mode: No access – MCR/MRC instructions have any effect. (R/W by programming the ICE by the JTAG (scan1) if JSDAEN=1	no
Secure thread-aware enable bit	0: debug is not possible for a particular thread 1: debug is possible for a particular thread	0	In functional mode or debug monitor mode: R/W by using MRC/MCR instruction (CP14) (only in secure supervisor mode) In Debug halt mode: No access – MCR/MRC instructions have any effect. (R/W by programming the ICE by the JTAG (scan1) if JSDAEN=1	no

Figure 61

Function Table

D	CK	Q[n+1]
0	↑	0
1	↑	1
X	↓	Q[n]

Logic Symbol



FIGURE 62

Function Table

D	SI	SE	CK	Q[n+1]
0	X	0	↑	0
1	X	0	↑	1
X	X	X	↓	Q[n]
X	0	1	↑	0
X	1	1	↑	1

Logic Symbol



figure 63



FIGURE 64



Figure 65.



FIGURE 66A



FIGURE 66B


544
570
530
SCAN CHAIN 4
CORE
ICE
Instruction Memory
(1)
CP14
CP14 Debug Status & Control Register
550
SCAN CHAIN 1
541
(3)
(2)
Debug TAP
580
JSDAEN
560

Figure 67



Figure 68

CP14 bits in Debug and Status Control register			meaning
Secure debug enable bit	Secure user-mode debug enable bit	Secure thread-aware debug enable bit	
0	X	X	No intrusive debug in entire secure world is possible. Any debug request, breakpoints, watchpoints, and other mechanism to enter debug state are ignored in entire secure world.
1	0	X	Debug in entire secure world is possible
1	1	0	Debug in secure user-mode only. Any debug request, breakpoints, watchpoints, and other mechanism to enter debug state are taken into account in user mode only. (Breakpoints and watchpoints linked or not to a thread ID are taken into account). Access in debug is restricted to what secure user can have access to.
1	1	1	Debug is possible only in some particular threads. In that case only thread-aware breakpoints and watchpoints linked to a thread ID are taken into account to enter debug state. Each thread can moreover debug its own code, and only its own code.

Figure 69A

CP14 bits in Debug and Status Control register			meaning
Secure trace enable bit	Secure user-mode debug enable bit	Secure thread-aware debug enable bit	
0	X	X	No observable debug in entire secure world is possible. Trace module (ETM) must not trace internal core activity.
1	0	X	Trace in entire secure world is possible
1	1	0	Trace is possible when the core is in secure user-mode only.
1	1	1	Trace is possible only when the core is executing some particular threads in secure user mode. Particular hardware must be dedicated for this, or re-use breakpoint register pair: Context ID match must enable trace instead of entering debug state.

Figure 69B



Figure 70

Method of entry	Entry when in non-secure world	entry when in secure world
Breakpoint hits	Non-secure prefetch abort handler	secure prefetch abort handler
Software breakpoint instruction	Non-secure prefetch abort handler	secure prefetch abort handler
Vector trap breakpoint	Disabled for non-secure data abort and non-secure prefetch abort interruptions. For other non-secure exceptions, prefetch abort.	Disabled for secure data abort and secure prefetch abort exceptions (1). For other exceptions, secure prefetch abort.
Watchpoint hits	Non-secure data abort handler	secure data abort handler
Internal debug request	Debug state in halt mode	debug state in halt mode
External debug request	Debug state in halt mode	debug state in halt mode

(1) see information on vector trap register,

(2) Note that when external or internal debug request is asserted, the core enters halt mode and not monitor mode.

Figure 71A

Method of entry	Entry in non-secure world	entry in secure world
Breakpoint hits	Non-secure prefetch abort handler	breakpoint ignored
Software breakpoint instruction	Non-secure prefetch abort handler	instruction ignored (1)
Vector trap breakpoint	Disabled for non-secure data abort and non-secure prefetch abort interruptions. For others interruption non-secure prefetch abort.	breakpoint ignored
Watchpoint hits	Non-secure data abort handler	watchpoint ignored
Internal debug request	Debug state in halt mode	request ignored
External debug request	Debug state in halt mode	request ignored
Debug re-entry from system speed access	not applicable	not applicable

(1) As substitution of BKPT instruction in secure world from non-secure world is not possible, non-secure abort must handle the violation.

Figure 71B